



**Central Institute of Fisheries Education
(Deemed University) Indian Council of Agricultural Research
Powarkheda – 461 110, DIST. Hoshangabad (MP) India**

Phone : 07574 – 227280, Fax : 07574 - 227208



F.No. 3-14/2006-07/Pkd/Works(PH)/
Date:29.02.08

To

Subject. : Invitation of quotation/ short tender for the ‘Construction of girls lobby & Renovation of toilets in hostel building at C.I.F.E. Center Powarkheda.

The Officer Incharge CIFE, Powarkheda, invites sealed quotations/ short tender for above mentioned works from the reputed/ registered contractors as per the following schedule.

1. Quotations must be submitted latest by : 14.30 hrs on **07st March **.2008
2. Quotations will be opened : 15.00 hrs on **07st March **.2008

Terms & conditions

- The quoted rates must be valid for six months
- Quotations/ short tender received after due date will not be entertained which may be collected from the Officer In charge, CIFE Centre Powarkheda or may be downloaded from CIFE Web site.
- Work contract tax and other taxes, if applicable should be mentioned clearly.
- Works must be completed before 25th March 2008 from the day receipt of work order.

Sealed quotations should reach to the following address by registered post not later than 14.30 hrs on 07th March 2008 to The Officer Incharge, Central Institute of Fisheries Education (Deemed University, I.C.A.R.), Powarkheda Centre, Powarkheda

- Quotation should be prepared as per the prescribed format.
- No advance shall be given. The payment will be made only after completion of all the works as per the specifications.
- Contractor should enclose following certificate/ documents along with the quotation- Registration Certificate, SaleTax/ Vat/ work Contract Tax No., PAN Card No. and Experience Certificate

The Officer, CIFE, Powarkheda Centre, Powarkheda reserves the right to accept or reject any or all quotations without assigning any reason thereof. No correspondence shall be entertained in this regards.

(Officer In-charge)

Encl: As above

Name of work :- Construction of Girl lobby with Toilets & Renovation of Old toilet in Hostel Building at C.I.F.E. Center Powarkheda.

S.No	Items	Qty.	Rate	Unit	Amount
1	Earth work in excavation in foundation trenches of drains (not exceeding 1.5 m in width or 10 sqm. On plan) including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.				
(a)	All kinds of soil.	10.00		Cum.	
2	Supplying and filling in plinth with local sand under floors including, watering, ramming consolidating and dressing complete.	8.00 Cum.		Cum.	
3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work upto plinth level.				
(a)	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	8.00 Cum.		Cum.	
(b)	1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	3.00 Cum.		Cum.	
4	Providing and laying in position cement concrete excluding the cost of centering, shuttering, finishing and reinforcement - All work upto plinth level.				
(a)	1:1½:3 (1 cement : 1½ coarse esand : 3 graded stone aggregate 20 mm nominal size)	5.00 Cum.		Cum.	
5	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete.				
(a)	Cold twisted bards.	700.00		Kg.	
6	Centering and shuttering including strutting, propping etc. and removal of form for :				
(a)	Foundations, footings, bases of columns etc. for mass concrete.	15.00		Sqm.	
		Sqm.			
(b)	Suspended floors, roofs, landings, balconies and access platform.	40.00 Sqm.		Sqm.	
7	Brick work with F.P.S. bricks of class designation 35 in foundations and plinth in :				
(a)	Cement mortar 1:6 (1 cement : 6 coarse sand)	25.00		Cum.	
8	Structural steel work welded in built up sections, trusses and framed work including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	1000.00 Kg.		Kg.	
9	15 mm cement plaster on the rough side of single of half brick wall of mix :				
(a)	1:4 (1 cement : 4 fine sand)	150.00		Sqm.	
10	6 mm cement plaster to ceiling of mix.				
(a)	1:3 (1 cement : 3 fine sand)	30.00		Sqm.	

11	Finishing walls with water proofing cement paint "Snowcem - Plus" of M/s. Snowcem India Ltd., or equivalent of required shade :				
(a)	New work (Two or more coats applied @3.84 kg/10 sqm.	80.00		Sqm.	
12	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade.				
(a)	New work (Two or more coats) over and including priming coat with cement primer.	100.00 Sqm.		Sqm.	
13	Painting with synthetic enamel paint (New work two or more coat)	50.00 Sqm.		Sqm.	
14	Providing and fixing on wall face unplasticised - Rigid PVC rain water pipes conforming to IS : 13592 Type A including jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion.				
(a)	110 mm diameter.	20.00		Mtr	
(b)	P/F NP 2 Class R.C.C. pipe.	30.00		Mtr	
15	Bend 87.5 ⁰				
(a)	P.V.C. Bend 100 mm	8.00		Each	
16	Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 Litre low level white PVC flushing cistern with manually controlled device (handle lever) conforming to IS : 7231 Parryware/Hindware/Seabird/Orient (Coral) with all fittings and fixtures complete including cutting and making good the walls and floors wherever required.				
(a)	White Vitreous china Orissa pattern W.C. pan of size 580 x 440 mm with integral type foot rests.	4.00 Nos.		Each	
17	Providing and fixing G.I. Pipes complete with G.I. Fittings and clamps, including cutting and making good the walls etc. (internal work)				
	Exposed on wall.				
(a)	15 mm dia nominal bore.	40.00		Mtr.	
(b)	20 mm dia. Nominal bore.	40.00		Mtr.	
(c.)	15 mm nominal bore.	9.00		Each	
(d)	15 mm nominal bore.	9.00		Each	
(d)	C.P. Snower rose. 100 mm.	6.00		Each	
18	Providing and fixing 1st quality ceramic glazed tiles conforming to IS : 13753 of minimum thickness of 5 mm of approved make like NITCO, ORIENT, SOMANY KAJARIA, or equivalent make in all colours, shades except begundy, bottle green, black of any size as approved by Engineer-in-charge in skirting, risers of steps and dados over 12 mm thick bed of Cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @3.3 kg. per sqm. including pointing in white cement mixed with pigment of matching shade complete.	120.00		Sqm.	

19	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 13755 of NITCO, ORIENT, KAJARIA, SOMANY or equivalent make in all colour, shades except White, ivory, Grey, Fume Red Brown laid on 20 mm thick bed of Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement and mathing pigments etc. complete.	60.00 Sqm.		Sqm.	
20	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 metres lead.				
(a)	In cement mortar.	1.00		Cum.	
21	Providing and fixing P.V.C. door with aluminium frame including all item with chodcet etc.	21.00 Sqm.		Sqm	
22	Boring pile holes 250 mm dia. S.U.R.	28.00		Mtr.	
23	Fixing chowkhats in existing opening including embedding chowkhats in floors or walls cutting masonry for holdfasts embedding hold fasts in cement concrete blocks with cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) painting two coats of coal tar to sides of chowkhats and making good the damages to walls and floors as required complete including disposal of rubbish to the dumping ground within 50 metres lead :				
(a)	Window chowkhats.	8.00		Each	
24	Making the oepning in brick masonry including dismantling, fixing chowkhats infloor or walls cutting masonry and fixing holdfasts in cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 stone aggregate 20 mm nominal size) painting two coats of coal tar to sides of chowkhats and making good the damages to walls and floors complete to match the existing surface.				
(a)	For Windows.	8.00		each	
25	Providing and fixing handwash basin single tap	2		each	
26	Providing and fixing P.V.C. water tank capacity of 1,000 liter	1.00		each	
27	P/F Mirror 45X60; 5mm thickness	2		each	